


Cuscinetti a sfera fila unica 400-47V-NICE - 400-47V-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/400-47v-nice>

400 Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



| BEARING | SUFFIX | BEARING DIMENSIONAL DATA | | | | BALLS | |
|---------|--------|--|--|---|---|-------|--------------|
| | | A BORE (in) (mm) +0.000/-0.000 | B O.D. (in) (mm) +0.0004/0.000 | C WIDTH (in) (mm) +0.010/-0.010 | D WIDTH (in) (mm) Reference | No. | Size (mm) |
| 400™ | 47V | 1.250 31.75 | 2.625 66.68 | 0.687 17.45 | 0.687 17.45 | 23 | 1/4 6.35 |

| WEIGHT W (lbs) (kg) | RADIAL CAPACITY | | | | | |
|------------------------------|------------------------|--------------|--------------|--------------|--------------|--------------|
| | REVOLUTIONS PER MINUTE | | | | | |
| | 50 | 100 | 200 | 300 | 600 | 1200 |
| | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) |
| 0.75 0.34 | 1020 4539 | 710 3160 | 490 2181 | 395 1758 | 275 1224 | 193 869 |

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3663952560175 |
| Diametro interno | 31.75 mm |
| Diametro esterno | 66.68 mm |
| Spessore | 17.45 mm |
| Peso | 340 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE