

Cuscinetti a sfera fila unica 602-V-NICE - 602-V-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/602-v-nice>

600 Series™ Unground Thrust Bearings **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- POLY-STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE



BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in)	BORE (in)	O.D. (in)	HEIGHT (in)		
602™	V	.375 9.53	+.010 10.15	1.384 26.59	-.359 9.12	14 5/32	0.06 0.03

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10	50	100	250	500	1000
(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
(N)	(N)	(N)	(N)	(N)	(N)
426	344	254	138	100	71
1896	1531	1130	614	445	318

Notes: Balls - Carbon Steel Grade 520
Washers - Carbon Steel Case Hard

Bands - Carbon Steel Soft
Bearings Oiled with a Rust Preventative
All Bearings Marked on Band with "Designation Nice USA" as Shown

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952560342
Diametro interno	9.53 mm
Diametro esterno	26.59 mm
Spessore	9.12 mm
Peso	30 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE