

Accessorio de supporti 7609-DL-NICE - 7609-DL-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/supporti/accessorio/7609-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE "H9E9" STANDARD
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE - 5000 - 8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE KEPT SEPARATE
- EXCELLENT APPLICABLE ANGLE OF CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET RADIUS - THIS WILL ENHANCE AS AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE HEATING AND NOISE ARE REDUCED.

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7609™	+0.0008 +0.020 -0.0000 -0.001	+0.0000 +0.0005 -0.0005 -0.013	+0.000 +0.005 -0.005 -0.19	0.0250 10.96	0.0825 3.30	1.009 39.83 0.138 5.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.982 50.00 27.74	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2095 11548	1025 4561	0.34 0.15

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7613™ and larger is +0.0005-0.0006 (+0.0005-0.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473400
Diametro interno	14.29 mm
Diametro esterno	25.63 mm
Spessore	15.88 mm
Peso	150 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE