


Accessorio de supporti 7610-DL-NICE - 7610-DL-NICE

<https://www.123cuscineti.it/cuscineti-supporti/supporti/accessorio/7610-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE "H9E9" STANDARD
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE - 5000 - 8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE OILED
- EXCELLENT APPLICABLE ANGLE OF CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET RADIUS - THIS WILL ENHANCE LIFE IN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EFFICIENCY, WEIGHT AND RELIABILITY ARE REQUIRED.



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7610™	.6250 15.88	1.7500 44.45	0.6250 15.88	0.0625 1.59	1.0000 25.40	0.138 3.46

PRINCIPLE DIMENSIONS					BASIC LOAD RATINGS		WEIGHT		
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Dynamic C _d (N)	Static C _s (lbf) (kg)	W (lb) (kg)	
0.042 1.07	1.922 48.82	1.922 48.82	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2196 11548	1025 4961	0.32 0.15

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473417
Diametro interno	15.88 mm
Diametro esterno	25.63 mm
Spessore	15.88 mm
Peso	150 g
Imballaggio	1

contatto@123cuscineti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE