


## Accessorio de supporti 7611-DL-NICE - 7611-DL-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/supporti/accessorio/7611-dl-nice>

**7600** Series™ Heavy Duty Precision Ground Radial Bearings With Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE 7TH DECIMAL
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE - 5000 - 8000 RPM
- TIMEDUR HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE OILED
- EXCELLENT APPLICABLE SINGLE LIP CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP FUL CRANK - THIS WILL ENHANCE AS AN OPTION
- PROVIDES FOR APPLICATIONS WHERE EXCESSIVE HEAT AND VIBRATION ARE REQUIRED.



BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7611™	.8675 17.46	1.7500 44.50	0.6250 15.88	0.0625 1.59	1.000 25.40	0.138 3.49

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C <sub>d</sub> (lb) (N)	Static C <sub>s</sub> (lb) (N)	W (lb) (kg)
0.042 1.07	1.922 49.82	1.992 50.59	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2196 11548	1025 4581	0.30 0.14

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)  
 ② Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015)  
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 ④ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473424
Diametro interno	17.46 mm
Diametro esterno	25.63 mm
Spessore	15.88 mm
Peso	140 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE