


Accessorio de supporti 7613-DL-NICE - 7613-DL-NICE

<https://www.123cuscineti.it/cuscineti-supporti/supporti/accessorio/7613-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE 7th DECIMAL
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000-8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHIMMEL BEARING
- EASILY APPLICABLE SINGLE LIP CONTACT BEARING
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP-FULL OPTION - THIS WILL BE SHIPPED AS AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EFFICIENCY, WEIGHT AND RELIABILITY ARE REQUIRED.



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7613™	.8125 20.64	2.5000 63.50	0.6250 15.88	0.0625 1.58	1.306 33.17	0.138 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Radius R (in) (mm)	Dynamic C ₁₀ (N)	Static C ₀ (N)	W (kg)
0.042 1.07	2.156 54.77	1.179 29.95	0.482 12.50	0.261 6.63	1/4-28	0.036 0.89	2970 13217	1360 6008	0.45 0.20

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473448
Diametro interno	20.64 mm
Diametro esterno	33.17 mm
Spessore	15.88 mm
Peso	200 g
Imballaggio	1

contatto@123cuscineti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE