

Accessorio de supporti 7618-DL-NICE - 7618-DL-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/supporti/accessorio/7618-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't)

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't)

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE - 5000 - 8000 RPM
- PRECISION MANUFACTURE
- GRADE 5 BEARING
- WIPER CASE STANDARD
- STANDARD SEALER STANDARD
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHIP END SYMBOL - THIS SIDE ORIENTABLE TO AN EXTENDED INNER RING
- RECOMMENDED FOR APPLICATIONS WHERE EXACTLY SPECIFIED DIMENSIONS AND SUPERIOR QUALITY ARE REQUIRED

| BEARING Ø | PRINCIPLE DIMENSIONS | | | | | |
|-----------|--|--|----------------------------|----------------------------|-------------------|------------------------------------|
| | BORE d (in) (mm) | O.D. D (in) (mm) | WIDTH B (in) (mm) | | F (in) (mm) | G (in) (mm) |
| 7618™ Ø | +0.0008 +0.000 -0.0000 -0.000 | +0.0000 +0.000 -0.0005 Ø -0.013 | +0.000 0.000 -0.005 | Ø0.000 Ø0.000 Ø0.000 | 0.0625 1.872 | +0.005 +0.13 -0.005 -0.13 |
| | 1.1250 28.58 | 2.5525 65.03 | 0.7500 19.05 | 0.0625 1.59 | 1.872 42.47 | 0.190 4.83 |

| PRINCIPLE DIMENSIONS | | | | | | BASIC LOAD RATINGS | | WEIGHT | | |
|----------------------|-------------------|-------------------|-------------------|-------------------|----------------------|--------------------------|-----------------------------|---|-------------------|--------------|
| H (in) (mm) | J (in) (mm) | K (in) (mm) | L (in) (mm) | M (in) (mm) | N 2 set screws | Radius R (in) (mm) | Dynamic C (lb) (N) | Static C ₀ (lb) (N) | W (lb) (kg) | |
| 0.065 1.65 | 2.768 70.25 | 1.417 35.98 | 1.417 35.98 | 0.605 15.37 | 0.261 6.63 | 1/4-28 6.35 | 0.055 0.89 | 5360 23852 | 2620 11659 | 0.80 0.36 |

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7613™ and larger is +0.0001-0.0006 (+0.0001-0.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nicol® Bearings.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3616060473493 |
| Diametro interno | 28.58 mm |
| Diametro esterno | 42.47 mm |
| Spessore | 19.05 mm |
| Peso | 360 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE