


Accessorio de supporti N6908-NICE - N6908-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/supporti/accessorio/n6908-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**



- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 2000 - 3000 RPM
- THROUGH HARDENED
- RETAINED DESIGN
- NYLON RETAINER STANDARD
- DOUBLE SEALED STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY SUFFIX	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm) Bolt Centers	H (in) (mm)
N6908™	B	0.500 12.70	1.6250 41.59	0.500 12.70	1.000 25.40	0.955 24.26	0.500 12.70	2.875 73.03	3.750 95.25

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT	
J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	O 2-Set Screws	P (in) (mm) Hole Dia.	S (in) (mm)	C (lbs) (N)	Cg (lbs) (N)	W (lbs) (kg)
1.875 47.63	0.438 11.11	0.688 17.48	1.000 25.40	0.062 1.57	1/4-28	0.4375 11.11	0.010 0.25	1610 7165	1010 4495	0.35 0.16

① When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B, for example 6904™B. Housings no longer carry part numbers.
② Tolerance for 6912 and larger is +.0000/-0.0006 (+000/-016) ③ Weights given are for greased and sealed version with flange mount.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952564791
Diametro interno	12.7 mm
Diametro esterno	41.28 mm
Spessore	12.7 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE