

## Accessorio de supporti N6916-NICE - N6916-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/supporti/accessorio/n6916-nice>

**6900** Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

**EASY TO USE DIMENSIONS**

- MEDIUM LOADS
- MAX SPEED RANGE: 2000 - 3000 RPM
- THROUGH HARDENED
- RETAINED DESIGN
- NYLON RETAINER STANDARD
- DOUBLE SEALER STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm) Bolt Centers	H (in) (mm)
	SUFFIX	+0.005	+0.000	+0.000	+0.000				
		+0.013	+0.000	+0.000	+0.000				
		-0.000	-0.000	-0.000	-0.000				
		-0.000	-0.000	-0.000	-0.000				
N6916™	B	1.000	2.0000	0.583	1.063	1.293	0.500	3.250	4.125
		25.40	50.80	14.29	26.99	32.84	12.70	82.55	104.78

PRINCIPLE DIMENSIONS								BASIC LOAD RATINGS		WEIGHT
J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	O 2-Set Screws	P (in) (mm) Hole Dia.	S (in) (mm)	C (lbs) (N)	C <sub>0</sub> (lbs) (N)	W (lbs) (kg)
2.250	0.438	0.688	1.125	0.062	10-32	0.4375	0.062	1870	1350	0.33
57.15	11.11	17.48	28.58	1.57		11.11	1.57	8322	6008	0.15

When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B, for example 6904™B. Housings no longer carry part numbers.

Tolerance for 6912 and larger is +.0000/-0.0006 (+000/-016) Weights given are for greased and sealed version with flange mount.

## CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952564814
Diametro interno	25.4 mm
Diametro esterno	50.8 mm
Spessore	14.29 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE