

Teste a snodo TSM MSL-07-F-DUNLOP - MSL-07-F-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/tsm/msl-07-f-dunlop>

MALE ROD ENDS 



MS SERIES: MS - MSS - MS SS

Description:
MS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 230M07Ph and forged 080M4, zinc plated and clear trivalent passivate and stainless steel 303, and forged 304. Inner Ring: Steel 070M20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100C76 heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studded and stainless steel options.

Possible Applications:
Medium/heavy industrial mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +200°C

Specification:
ELV & RoHS compliant

Housing: Steel 230M07Ph (Sizes 04 - 07) Forged 080M4 (Sizes 08-12) Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate

Balls: Bearing Steel 100C76, Case Hardened and Electro-less Nickel Plated

Liners: High Strength PTFE Composite

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MSL-07F		7/16	7/16 BSF	0.562	0.437	1.250	2.125	1.375	14.90	19,900

Interchange table

Dunlop	Rose	Aurora	Askubal	SKF	ASAHI	IKO	Fluro
MS-M (metric)	MHC	MM-M-T and MB-M-T	KA-P	SAKB-P	JAM-EC	POS-EC	GASW
MS (imperial)	RMC	MM-T and MB-T	-	-	-	POSB-EC	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MS-04-SS'

CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060550194
Diametro interno	11.1125 mm
Diametro esterno	31 mm
Spessore	14.2748 mm
Tipo	TSM
Il filo	Filetto sinistro
Lubrificazione	NA
Carico statico	0.0199 kN
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE