


Teste a snodo SI FSL-08-F-DUNLOP - FSL-08-F-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/fsl-08-f-dunlop>

FEMALE ROD ENDS 



FS SERIES: FS - FSS - FS SS

DESCRIPTION:
FS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the lower material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

MATERIAL SPECIFICATIONS:
Housing: Steel Z30M07Pb (S100), 0.4% CR, Forged 080M40 (S200) 0.2% Zn, Zinc Plated and Clear Trivalent Passivate
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Liner: High Strength PTFE Composite

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Sludged and stainless steel options.

Possible Applications:
Medium/heavy industrial, mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +260°C

Specification:
ELV & RoHS compliant

| Part No. Right Hand | Part No. Left Hand | Bore Size | Thread | W | H | D | L1 | L2 | O | AF | Static Load Rating (Newtons) Radial |
|---------------------|--------------------|-----------|---------|-------|-------|-------|-------|-------|-------|-------|-------------------------------------|
| FSL-08F | | 1/2 | 1/2 BSF | 0.625 | 0.500 | 1.375 | 2.125 | 1.187 | 17.75 | 0.750 | 23,600 |

Interchange table

| Dunlop | Rose | Aurora | Askubal | SKF | Asahi | IKO | Fluro |
|---------------|------|-------------------|---------|-------|---------|--------|-------|
| FS-M (metric) | MFC | MW-M-T and MG-M-T | KI-P | SKR-F | JAF-EC | PHS-EC | QISW |
| FS (imperial) | RFC | MW-T and MG-T | - | - | PHSG-EC | - | - |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|----------------|
| Marchio | DUNLOP |
| N° Ean13 | 3616060554567 |
| Diametro interno | 12.7 mm |
| Diametro esterno | 0.625 mm |
| Spessore | 0.5 mm |
| Tipo | SI |
| Il filo | Filetto destro |
| Lubrificazione | con |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE