

Teste a snodo SI FSX-06-DUNLOP - FSX-06-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/fsx-06-dunlop>

FEMALE ROD ENDS 



DESCRIPTION:
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Liner: High Strength PTFE Composite

Features:
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

Temperature Range:
-200°C to +240°C

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Specification:
ELV & RoHS compliant

| Part No. Right Hand | Part No. Left Hand | Bore Size | Thread | W | H | D | L1 | L2 | AF | Static Load Rating (Newtons) Radial |
|---------------------|--------------------|-----------|---------|-------|-------|-------|-------|-------|-------|-------------------------------------|
| FSX-06 | | 3/8 | 3/8 UNF | 0.500 | 0.406 | 1.125 | 1.625 | 0.937 | 0.542 | 34800 |

Interchange table

| Dunlop | Aurora | Fluro |
|----------------|-------------------|-------|
| FSX-M (Metric) | AM-M-T and AD-M-T | GUSW |
| FSX (Imperial) | AM-T and AD-T | |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|----------------|
| Marchio | DUNLOP |
| N° Ean13 | 3616060556349 |
| Diametro interno | 9.525 mm |
| Diametro esterno | 28.575 mm |
| Spessore | 12.7 mm |
| Tipo | SI |
| Il filo | Filetto destro |
| Lubrificazione | NA |
| Carico statico | 34.8 kN |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE