

## Teste a snodo SI FXL-16-FG-DUNLOP - FXL-16-FG-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/fxl-16-fg-dunlop>

FEMALE ROD ENDS 



**FX SERIES**

**Description:**  
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

**Material Specifications:**  
Housing: S17M40, heat treated to 80/90 tons/in<sup>2</sup> tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

**Features:**  
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

**Possible Applications:**  
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

**Temperature Range:**  
-40°C to +150°C

**Specification:**  
ELV & RoHS compliant

Housing: Forged S17M40, Heat Treated 80/90 tons/in<sup>2</sup> tensile and Phosphated all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newton) Radial
	FXL-16FG	1.0000	1.375	1.0000	1.375	3.000	4.125	2.125	1.625	1 1/4 BSF	24	150250

**Interchange table**

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060556394
Diametro interno	7500 mm
Diametro esterno	875 mm
Spessore	812 mm
Tipo	SI
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE