





## Teste a snodo SI AL-SA-010-DUNLOP - AL-SA-010-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/al-sa-010-dunlop>

FEMALE ROD ENDS 



**FEMALE ROD ENDS**

**Housing:** Aluminum A6061, Black Anodized

**AL SERIES**

**Description:**  
AL-Series is our 3-piece aluminum light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

**Material Specifications:**  
Housing: Aluminum A6061, black anodized. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

<b>Features</b> Metric bore & thread sizes Low friction Self-lubricating Good wear resistance Excellent moisture resistance No maintenance Light weight	<b>Possible Applications</b> Light industrial/mechanical applications Weight restricted applications Linear movement sensors	<b>Temperature Range</b> -30°C to +170°C <b>Specification</b> ELV & RoHS compliant
--	---	---

**Race Ball:** GR-nylon, LV-3H  
Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-010		5	M5x0.80	8	8.00	16	27.0	14.0	9.0	9.0	9,340

### CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060556431
Diametro interno	5 mm
Diametro esterno	8 mm
Spessore	6 mm
Tipo	SI
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE