




Teste a snodo SI AL-SA-106-LH-DUNLOP - AL-SA-106-LH-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/al-sa-106-lh-dunlop>

FEMALE ROD ENDS 



FEMALE ROD ENDS



AL SERIES

Description:
AL-Series is our 3-piece aluminium light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminium A6061, black anodised. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric bore & thread sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance
Light weight

Possible Applications:
Light industrial/mechanical applications
Weight restricted applications
Linear movement sensors

Temperature Range:
-30°C to +170°C

Specification:
ELV & RoHS compliant

Housing: Aluminium A6061, Black Anodised Race: GR-nylon, LV-3H Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-106		3	M3x0.50	6	4.50	12	18.5	7.0	5.2	6.5	3,040

CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060556608
Diametro interno	3 mm
Diametro esterno	6 mm
Spessore	4.5 mm
Tipo	SI
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE