



Teste a snodo SI DB-SA-168-DUNLOP - DB-SA-168-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/db-sa-168-dunlop>

MALE ROD ENDS 



DB SERIES: DBM - DBI

Description:
DB-Series is our 3-piece 'dog bone' range of rod ends primarily based on our MP-Series with regards to function and structure. A wide range of preset centre distances are available. Suitable for light to medium industrial/mechanical load applications requiring low friction, with good wear resistance and available in both metric and imperial bore sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Steel 230M07PB zinc plated and clear trivalent passivate.
Race: GR-Nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric & imperial thread & bore sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance

Possible Applications:
Light to medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles

Temperature Range:
-30°C to +170°C

Specifications:
ELV & RoHS compliant

Housing: Steel 230M07PB, Zinc Plated and Clear Trivalent Passivate
Race: GR-Nylon, LV-3H
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No.	Bore Size	C	W	H	D	Ø	Liner	Static Load Rating (Newtons) Radial
DB-SA-168	3/8	120.0	0.500	0.400	1.000	0.016	GR-NYLON	16,900

CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060556875
Diametro interno	9.52 mm
Diametro esterno	120 mm
Spessore	0.5 mm
Tipo	SI
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE