


Snodi sferici GE GE100-FW-DUNLOP - GE100-FW-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge100-fw-dunlop>

SPHERICAL BEARINGS 





GE FW SERIES

Description:
GE-FW-Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the balls and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electro-less nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

Features:
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications:
Medium/heavy industrial mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control.

Temperature Range:
-52°C to +121°C

Specification:
E.V. & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened Race: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Ball: PTFE Fabric

| Part No. Unsealed | Part No. Sealed | Bore Size | W | H | D | Static Load Rating (Newtons) Radial |
|-------------------|-----------------|-----------|----|----|-----|-------------------------------------|
| GE100FW | | 100 | 85 | 95 | 160 | 3,075,000 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|----------------|
| Marchio | DUNLOP |
| N° Ean13 | 3616060557391 |
| Diametro interno | 100 mm |
| Diametro esterno | 160 mm |
| Spessore | 85 mm |
| Tipo | GE |
| Il filo | Filetto destro |
| Lubrificazione | con |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE