


## Snodi sferici GE GEZ008-ES-2RS-DUNLOP - GEZ008-ES-2RS-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/gez008-es-2rs-dunlop>

SPHERICAL BEARINGS 



**GEZ ES SERIES**

**Description:**  
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS<sub>2</sub> for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.


**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS<sub>2</sub>. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

**Features:**  
Metric bore sizes  
Low cost  
Maintenance required  
Up to 140mm bore sizes available

**Possible Applications:**  
Light to heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Hydraulic applications

**Temperature Range:**  
-34°C to +121°C

**Specifications:**  
ELV & RoHS compliant



**Outer Ring:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS<sub>2</sub>.

**Ball:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

**Seals:** Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GEZ008ES-2RS	1/2	11.100	9.525	22.225	41,000

### CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060558039
Diametro interno	12.7 mm
Diametro esterno	22.225 mm
Spessore	11.1 mm
Tipo	GE
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE