

Snodi sferici GE GEZ014-ES-2RS-DUNLOP - GEZ014-ES-2RS-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/gez014-es-2rs-dunlop>

SPHERICAL BEARINGS 



GEZ ES SERIES

Description:
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂.

Ball: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seals: Polyurethane



Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GEZ014ES-2RS	7/8	19.431	16.662	36.513	127,000

CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	5059161262340
Diametro interno	22.22 mm
Diametro esterno	36.51 mm
Spessore	16.66 mm
Tipo	GE
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE