

## Snodi sferici GE GE40-UK-DUNLOP - GE40-UK-DUNLOP

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge40-uk-dunlop>

SPHERICAL BEARINGS





**GE UK SERIES**

**Description:**  
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.  
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.  
Seals: Polyurethane.

<b>Features</b>	<b>Possible Applications</b>	<b>Temperature Range</b>
Metric bore sizes Low friction High shock loads Extended wear life No maintenance	Medium-heavy industrial mechanical applications Construction equipment Agricultural equipment Recreational vehicles High precision motion control	-200°C to +260°C <b>Specification</b> ELV & RoHS compliant

**Outer Ring:** Bearing Steel 100Cr6, Case Hardened      **Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated  
**Liner:** High Temperature PTFE Composite

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE40UK		40	28	22	62	290,000

### CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060558510
Diametro interno	40 mm
Diametro interno	1.575" inch
Diametro esterno	62 mm
Diametro esterno	2.441" inch
Spessore	28 mm
Spessore	1.102" inch
Tipo	GE
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE