

## Gusci a rullini BA2212-Z-IKO - BA2212-Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/ba2212-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. $d_2$	Housing bore dia. $D_1$	$C_1$	$C_2$	$C_3$	rpm		
34.925 (1 3/8)	41.275 (1 5/8)	19.05 (.750)	Max.	Min.	Max.	Min.	16900	33500	15000	RB 1812

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060601391
Diametro interno	34.925 mm
Diametro interno	1 3/8" inch
Diametro esterno	41.275 mm
Diametro esterno	1 5/8" inch
Spessore	19.05 mm
Spessore	3/4" inch
Velocità limite	10000 rpm
Carico dinamico	16.9 kN
Carico statico	33.5 kN
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE