


Cuscinetti conico 2559-2525-TIMKEN - 2559-2525-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/2559-2525-timken>

TYPE TS



Dimensione	Dimensione	Abbronzatura e Fillet Dimensione	
d - Base	30.163 mm 1.1875 in	k - Case Backhoe "to Case" Radius ²	0.762 mm 0.030 in
D - Cap Outer Diameter	72.022 mm 2.8351 in	r - Cap Backhoe "to Case" Radius ²	0.75 mm 0.030 in
B - Case Width	25.267 mm 0.9943 in	A ₁ - Cap Front Face Backing Diameter	36.46 mm 1.431 in
C - Cap Width	19.050 mm 0.7500 in	A ₂ - Cap Back Face Backing Diameter	37.06 mm 1.459 in
T - Sealing Width	23.813 mm 0.9375 in	D ₁ - Cap Front Face Backing Diameter	66.02 mm 2.601 in
Basic Load Ratings		D ₂ - Cap Back Face Backing Diameter	62.99 mm 2.48 in
C ₉₀ - Dynamic Radial Rating (90 million revolutions) ³	4850 lbf 21 780 N	Ab - Cage Case Front Face Clearance	5.5 mm 0.216 in
C ₁₀ - Dynamic Radial Rating (1 million revolutions) ³	43862 lbf 195700 N	Aa - Cage Case Back Face Clearance	0.5 mm 0.02 in
C ₀ - Static Radial Rating	31300 lbf 14000 N	a - Effective Center Location ³	0.5 mm 0.02 in
C _{up} - Dynamic Thrust Rating (90 million revolutions) ³	2280 lbf 10200 N		
Factors			
K - Factor ⁷	2.54		
v - ISO Factor ⁸	0.27		
V - ISO Factor ⁸	2.19		
C ₁ - Heat Generation Factor (Steady Rotation)	23.6		
C ₂ - Heat Generation Factor (300 Revs/Min)	8.6		
C ₃ - Geometry Factor	0.0676		

CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3616060668097
Diametro interno	30.163 mm
Diametro esterno	72.022 mm
Spessore	23.813 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE