


Cuscinetti conico NN3014-K-NTN - NN3014-K-NTN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/nn3014-k-ntn>



Double Row Cylindrical Roller Bearing w/ Tapered Bore - Type NN - Dimensions

Technical Specifications		Dimensional Specifications	
Type	Cylindrical Roller Bearing		2.7558 in 70.000 mm
Bore Type	Tapered		4.3307 in 110.000 mm
Material	Hardened Alloy Steel		
Cage Material	High Strength, 2 piece, Molded Steel	B	1.1811 in 30.000 mm
Limiting Speed - Oil	6900 RPM		
Limiting Speed - Grease	5800 RPM	C	1.1811 in 30.000 mm
Taper	1:12	Ew	3.9370 in 100.000 mm
Precision	ABEC 3	r	0.0433 in 1.100 mm
Configuration	Open		
Oil Hole	with Oil Hole	da min	3.0118 in 76.500 mm
Radial Internal Clearance	CN	db min	3.1102 in 79.000 mm
Static Load Rating	32000 lbf 143200 N 143.00 kN	Da max	3.9764 in 101.000 mm
Dynamic Load Rating	21200 lbf 94500 N 94.50 kN	Db min	3.9764 in 101.000 mm
Enclosure	Open	Db max	4.0748 in 103.500 mm
Operating Temperature Range	-40 to 250 °F -40 to 120 °C	raa max	0.0394 in 1.000 mm

CARATTERISTICHE DEL PRODOTTO

Marchio	NTN
N° Ean13	3616060804792
Diametro interno	70 mm
Diametro esterno	110 mm
Spessore	30 mm
Carico dinamico	94.5 kN
Carico statico	143 kN
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE