

## Pasta guarnizioni 5207-250ML-LOCTITE - 5207-250ML-LOCTITE

<https://www.123cuscinetti.it/lubrificanti-adesivi/adesivi/pastaguarnizioni/5207-250ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Étanchéité plane, moyennement flexible
NOM	LOCTITE 5207
CONDITIONNEMENT	Tube 250 ml
COMMENTAIRE	
APPROBATION*	

#### Description

LOCTITE® 5207 is a red, fluorescent, medium strength, medium viscosity, anaerobic sealant typically used as a form-in-place gasket on rigid flanged connections, e.g. gearbox and engine casings, etc. It seals close fitting joints between rigid metal faces and flanges and provides resistance to low pressures immediately after assembly of flanges.

#### Avantages

Fluorescent  
Medium strength  
Medium viscosity  
Provides resistance to low pressures immediately after assembly of flanges  
Maintains flexibility after exposure to high temperatures

#### Caractéristiques

Fluorescent dimethacrylate ester acrylic sealant used as a form-in-place gasket on rigid flanged connections, e.g. gearbox and engine casings, etc.

## CARATTERISTICHE DEL PRODOTTO

Marchio	LOCTITE
N° Ean13	3616060812186
Peso	250 g
Imballaggio	-

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE