


Cuscinetti conico 938-932-JTEKT - 938-932-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/938-932-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|----------------------|----------------------|----------------------|-------------------------|-----------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r_a</i> | <i>r_b</i> | <i>r₁</i> | <i>C_r</i> | <i>C₁₀</i> | Grease lub. | Oil lub. |
| 114.300 | 212.725 | 66.675 | 66.675 | 53.975 | 7.1 | 3.2 | | 450 | 674 | 1 800 | 2 400 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|----------------------|----------------------|----------------------|---------------------------|---------------------------|----------|----------------------|----------------------|--------------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d_a</i> | <i>d_b</i> | <i>D_a</i> | <i>D_b</i> | <i>r_a</i> max. | <i>r_b</i> max. | <i>e</i> | <i>Y₁</i> | <i>Y₂</i> | Inner ring | Outer ring |
| 938 | 932 | 47.6 | 141.0 | 128.0 | 187.0 | 193.0 | 7.1 | 3.2 | 0.33 | 1.84 | 1.01 | 5.96 | 4.07 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 4549250209734 |
| Diametro interno | 114.3 mm |
| Diametro esterno | 212.72 mm |
| Spessore | 53.9 mm |
| secondo spessore | 66.6 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE