


Cuscinetti conico 30318-R-JTEKT - 30318-R-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/30318-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
90	190	46.5	43	36	336	407	2 100	2 700	30318R					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} max.	D _{1a} min.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	37.2	108	113	176	165	177	5	10.5	3	2.5	0.35	1.73	0.95	5.78

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	4549250122347
Diametro interno	90 mm
Diametro interno	3.543" inch
Diametro esterno	190 mm
Diametro esterno	7.48" inch
Spessore	46.5 mm
Spessore	1.831" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE