

## Cuscinetti conico 32919-JR-JTEKT - 32919-JR-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/32919-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                    |                |                      |       |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|-------|
| d                                      | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                    |                |                      |       |
| 95                                     | 130                | 23                       | 23                   | 18                      | 104                  | 186                  | 2 600                | 3 500                                | 32919JR              |                           |                    |                |                      |       |
| Dimension series to ISO 955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors |                | (Refer. 1) Mass (kg) |       |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min.    | D <sub>1a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min.                 | r <sub>1a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                      |       |
| 29C                                    | 23.5               | 103.5                    | 102                  | 121.5                   | 119                  | 125                  | 5                    | 5                                    | 1.5                  | 1.5                       | 0.36               | 1.68           | 0.92                 | 0.876 |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | JTEKT         |
| N° Ean13         | 3663952409702 |
| Diametro interno | 95 mm         |
| Diametro esterno | 130 mm        |
| Spessore         | 23 mm         |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE