

Cuscinetti conico 30320-D-JTEKT - 30320-D-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/30320-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.		
100	215	51.5	47	34	318	374	1 500	2 100	30320D	

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	65.9	118	121	201	183	204	5	17	3	2.5	0.81	0.74	0.41	8.02

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	4549250122415
Diametro interno	100 mm
Diametro interno	3.937" inch
Diametro esterno	215 mm
Diametro esterno	8.465" inch
Spessore	51.5 mm
Spessore	2.028" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE