

## Cuscinetti conico 32324-JR-JTEKT - 32324-JR-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/32324-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                     | Basic load ratings (kN) |                     |                     |                     | Limiting speeds (min <sup>-1</sup> ) |                     | Bearing No. <sup>1)</sup> |                    |                |                      |      |
|--|--------------------|--------------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|---------------------|---------------------------|--------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                   | C                       | C <sub>r</sub>      | C <sub>0r</sub>     | Grease lub.         | Oil lub.                             |                     |                           |                    |                |                      |      |
| 120                                    | 260                | 90.5                     | 86                  | 69                      | 800                 | 1 110               | 1 500               | 2 000                                | 32324JR             |                           |                    |                |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                     |                         |                     |                     |                     |                                      |                     | Constant e                | Axial load factors |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>a</sub> min.      | d <sub>a</sub> max. | D <sub>a</sub> min.     | D <sub>a</sub> max. | S <sub>a</sub> min. | S <sub>a</sub> max. | r <sub>a</sub> min.                  | r <sub>a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                      |      |
| 260                                    | 62.7               | 138                      | 148                 | 246                     | 213                 | 239                 | 9                   | 21.5                                 | 3                   | 2.5                       | 0.35               | 1.74           | 0.96                 | 22.2 |

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | JTEKT         |
| N° Ean13         | 4549250125355 |
| Diametro interno | 120 mm        |
| Diametro esterno | 260 mm        |
| Spessore         | 90.5 mm       |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE