

Cuscinetti conico 30232-JR-JTEKT - 30232-JR-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/30232-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
160	290	52	48	40	4	3	542	750	1 200	1 600	30232JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4GB	56.3	178	189	276	252	269	8	12	3	2.5	0.44	1.38	0.76	14.1

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952421247
Diametro interno	160 mm
Diametro interno	6.299" inch
Diametro esterno	290 mm
Diametro esterno	11.417" inch
Spessore	52 mm
Spessore	2.047" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE