


Cuscinetti conico 26112-26283-JTEKT - 26112-26283-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/26112-26283-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|-------------------------------|-------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _a max. | <i>r</i> _b max. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 28.575 | 72.000 | 19.000 | 18.900 | 15.875 | 1.6 | 1.6 | 47.5 | 49.6 | 5 900 | 7 800 |

| Bearing No. | | Load center (mm) <i>a</i> | Mounting dimensions (mm) | | | | | | Constant <i>e</i> | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------------------|--------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|-------------------------------|----------------------|-----------------------|-----------------------|-----------------------|------------|
| Inner ring | Outer ring | | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 26112 | 26283 | 15.3 | 37.0 | 35.0 | 62.0 | 65.0 | 1.6 | 1.6 | 0.36 | 1.67 | 0.92 | 0.217 | 0.163 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952425887 |
| Diametro interno | 28.575 mm |
| Diametro interno | 1 1/8" inch |
| Diametro esterno | 72 mm |
| Diametro esterno | 2.835" inch |
| Spessore | 19 mm |
| Spessore | 0.748" inch |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE