



Cuscinetti conico 6382-6320-JTEKT - 6382-6320-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/6382-6320-jtekt>

Single-row tapered roller bearings inch series 



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|-------|-------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r_a | r_b | C_r | C_{10} | Grease lub. | Oil lub. |
| 63.500 | 135.755 | 53.975 | 56.007 | 44.450 | 4.3 | 3.2 | 286 | 357 | 3 000 | 4 000 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|------------|------------|--------------------|-------|--------------------|------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| 6382 | 6320 | 34.8 | 84.0 | 77.0 | 117.0 | 126.0 | 4.3 | 3.2 | 0.32 | 1.85 | 1.02 | 2.29 | 1.39 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952428512 |
| Diametro interno | 63.5 mm |
| Diametro esterno | 135.755 mm |
| Spessore | 53.975 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE