


Cuscinetti a rullini BHTM1525-JTEKT - BHTM1525-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/bhtm1525-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾	
F_w	D	C	b min.	C_{10}	C_{90}	Oil lub.	Caged type	
							With open ends	With closed end
15	22	25	—	17.7	25.0	23 000	BHTM1525	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	14.989	15.000	21.972	21.993	26	—

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952470252
Diametro interno	15 mm
Diametro esterno	22 mm
Spessore	25 mm
Peso	26 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE