


## Cuscinetti a rullini BHTM1612-JTEKT - BHTM1612-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/bhtm1612-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type		
							With open ends	With closed end	
16	24	12	—	8.00	8.45	21 000	<b>BHTM1612</b>		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (f6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	23.972	23.993	15	—

## CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952470351
Diametro interno	16 mm
Diametro esterno	24 mm
Spessore	12 mm
Peso	15 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE