


Cuscinetti a rullini BHTM1616A-JTEKT - BHTM1616A-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/bhtm1616a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F _w	D	C	b min.	C ₀	C _{0r}	Oil lub.	Caged type With open ends With closed end
16	24	16	13.3	12.2	14.9	21 000	BHTM1616A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	23.991 ⁴⁾	24.012 ⁴⁾	20	23

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952470368
Diametro interno	16 mm
Diametro esterno	24 mm
Spessore	16 mm
Peso	20 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE