

Cuscinetti a rullini 20BTM2620A-JTEKT - 20BTM2620A-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/20btm2620a-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|----------|---------------------------|-----------------|
| F _w | D | C | b min. | C ₀ | C _{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 20 | 26 | 20 | — | 15.2 | 26.4 | 18 000 | 20BTM2620A | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (f6) | | Housing bore dia. (H7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 19.987 | 20.000 | 25.972 | 25.993 | 24 | — |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952470887 |
| Diametro interno | 20 mm |
| Diametro esterno | 26 mm |
| Spessore | 20 mm |
| Peso | 24 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE