


Cuscinetti a rullini BTM2015-JTEKT - BTM2015-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/btm2015-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|----------|---------------------------|-----------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 20 | 27 | 15 | — | 13.1 | 18.7 | 18 000 | BTM2015 | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 19.870 | 20.000 | 25.972 | 25.993 | 20 | — |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952470924 |
| Diametro interno | 20 mm |
| Diametro esterno | 27 mm |
| Spessore | 15 mm |
| Peso | 20 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE