

Cuscinetti a rullini 22BTM2812-JTEKT - 22BTM2812-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/22btm2812-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F _w	D	C	b min.	C ₁₀	C ₉₀	Oil lub.	Caged type With open ends With closed end
22	28	12	9.3	9.10	13.5	16 000	22BTM2812

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φG) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	27.972	27.993	14	16

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952471075
Diametro interno	22 mm
Diametro interno	0.866" inch
Diametro esterno	28 mm
Diametro esterno	1.102" inch
Spessore	12 mm
Spessore	0.472" inch
Peso	14 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE