

Cuscinetti a rullini RNA4901R-JTEKT - RNA4901R-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/rna4901r-jtekt>

Machined ring needle roller bearings

F_w 29 – 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|------------|------------|------------|-------------------------|-----------------|--|--------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Without inner ring | |
| 16 | 12 | 24 | 13 | 10.2 | 11.8 | 27 000 | RNA4901R | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | | | |
| | d_a min. | D_a max. | r_a max. | 0.018 | 0.027 | IRM121613 | | |
| | 14 | 22 | 0.3 | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952477688 |
| Diametro interno | 16 mm |
| Diametro esterno | 24 mm |
| Spessore | 13 mm |
| Peso | 18 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE