

Cuscinetti a rulli NQ24-20AD-JTEKT - NQ24-20AD-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/rulli/nq24-20ad-jtekt>

Machined ring needle roller bearings 

F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-------|-------|-------|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Grease lub. | Without inner ring | |
| 24 | — | 32 | 20 | — | 17.3 | 26.5 | 19 000 | NQ24/20AD | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | — | | | |
| | d_1 | D_1 | r_1 | — | — | — | | | |
| | max. | max. | max. | — | 0.040 | — | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952482330 |
| Diametro interno | 24 mm |
| Diametro esterno | 32 mm |
| Spessore | 20 mm |
| Peso | 40 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE