


Cuscinetti a rullini NQIS25-22-JTEKT - NQIS25-22-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nqis25-22-jtekt>

Machined ring needle roller bearings 

F_w 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	Without inner ring	
32	25	47	22	31.2	41.4	14 000	—	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
NQIS25/22				27	45	0.3	0.123	0.167	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952482842
Diametro interno	25 mm
Diametro esterno	47 mm
Spessore	22 mm
Peso	167 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE