


Cuscinetti a rulli NA5920-JTEKT - NA5920-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/rulli/na5920-jtekt>

Machined ring needle roller bearings 

F_w 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|-----|-----|-----|-------|-------------------------|-----------------|--|--------------------|--------------------|-------------|
| F_w | d | D | B | B_1 | C_r | C_{10} | Oil lub. | Without inner ring | Without inner ring | |
| 115 | 100 | 140 | 54 | — | 189.0 | 418.0 | 4 000 | — | — | |
| Mounting dimensions (mm) | | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | | Without inner ring | With inner ring | | | | |
| NA5920 | | | | | 106.5 | 133.5 | 1 | 1.49 | 2.53 | IRM10011554 |

[Note] 1) Limiting speeds of bearing number NA49...LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952484242 |
| Diametro interno | 100 mm |
| Diametro esterno | 140 mm |
| Spessore | 54 mm |
| Peso | 2530 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE