

Cuscinetti a sfera fila unica 23192-R-JTEKT - 23192-R-JTEKT

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/23192-r-jtekt>

Boundary dimensions

Asymmetrical rollers: R/R, R1/R2R, R1/R2
Symmetrical rollers: R/R
Taper bore: KoK30

23192R / 23192R1R1 / 23192R1R2 / 23192R1R2H1 / 23192R1R2H2 / 23192R1R2H3 / 23192R1R2H4 / 23192R1R2H5 / 23192R1R2H6 / 23192R1R2H7 / 23192R1R2H8 / 23192R1R2H9 / 23192R1R2H10 / 23192R1R2H11 / 23192R1R2H12 / 23192R1R2H13 / 23192R1R2H14 / 23192R1R2H15 / 23192R1R2H16 / 23192R1R2H17 / 23192R1R2H18 / 23192R1R2H19 / 23192R1R2H20 / 23192R1R2H21 / 23192R1R2H22 / 23192R1R2H23 / 23192R1R2H24 / 23192R1R2H25 / 23192R1R2H26 / 23192R1R2H27 / 23192R1R2H28 / 23192R1R2H29 / 23192R1R2H30 / 23192R1R2H31 / 23192R1R2H32 / 23192R1R2H33 / 23192R1R2H34 / 23192R1R2H35 / 23192R1R2H36 / 23192R1R2H37 / 23192R1R2H38 / 23192R1R2H39 / 23192R1R2H40 / 23192R1R2H41 / 23192R1R2H42 / 23192R1R2H43 / 23192R1R2H44 / 23192R1R2H45 / 23192R1R2H46 / 23192R1R2H47 / 23192R1R2H48 / 23192R1R2H49 / 23192R1R2H50 / 23192R1R2H51 / 23192R1R2H52 / 23192R1R2H53 / 23192R1R2H54 / 23192R1R2H55 / 23192R1R2H56 / 23192R1R2H57 / 23192R1R2H58 / 23192R1R2H59 / 23192R1R2H60 / 23192R1R2H61 / 23192R1R2H62 / 23192R1R2H63 / 23192R1R2H64 / 23192R1R2H65 / 23192R1R2H66 / 23192R1R2H67 / 23192R1R2H68 / 23192R1R2H69 / 23192R1R2H70 / 23192R1R2H71 / 23192R1R2H72 / 23192R1R2H73 / 23192R1R2H74 / 23192R1R2H75 / 23192R1R2H76 / 23192R1R2H77 / 23192R1R2H78 / 23192R1R2H79 / 23192R1R2H80 / 23192R1R2H81 / 23192R1R2H82 / 23192R1R2H83 / 23192R1R2H84 / 23192R1R2H85 / 23192R1R2H86 / 23192R1R2H87 / 23192R1R2H88 / 23192R1R2H89 / 23192R1R2H90 / 23192R1R2H91 / 23192R1R2H92 / 23192R1R2H93 / 23192R1R2H94 / 23192R1R2H95 / 23192R1R2H96 / 23192R1R2H97 / 23192R1R2H98 / 23192R1R2H99 / 23192R1R2H100

Spherical roller bearings

Bearing No.	Boundary dimensions(mm)			Basic load ratings(kN)	Fatigue load limit(kN)		Limiting speeds(min-1)
	d	D	B		Cr	C0r	
23192R	460	760	240	6510	10800	648	310

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3616060672384
Diametro interno	460 mm
Diametro esterno	760 mm
Spessore	240 mm
Velocità limite	310 rpm
Carico dinamico	6510 kN
Carico statico	10800 kN
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE