


## Gusci a rullini BA1610-ZOH-IKO - BA1610-ZOH-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/ba1610-zoh-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



BA--Z BHA--Z

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g				
	Standard	Mass (Ref.) g	Closed end													
25.400 (1)	--	--	--	<b>BA 1610 Z</b>	22	--	--	--	--	--	--	--				
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Ball dynamic load rating		Ball static load rating		Allowable rotational speed <sup>(1)</sup>		Assembled inner ring		
$F_w$	$D$	$C$	$t$	Shaft dia. mm	Housing bore dia. mm	Ball dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring							
25.400	31.750	15.881	2.8	25.400	25.387	31.764	31.739	11 900	18 100	15 000						

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952172804
Diametro interno	25.4 mm
Diametro esterno	31.75 mm
Spessore	15.88 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE