


Gusci a rullini BAM116-IKO - BAM116-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam116-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
17.462 ($\frac{11}{16}$)	—	—	—	—	—	—	—	BAM 116	B.4	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring		
F_w	D	C	b_2	Shaft dia. h_8	Housing bore dia. J_7	C	C_0	rpm			
17.462 ($\frac{11}{16}$)	22.225 ($\frac{7}{8}$)	9.521 (.375)	1.3	17.462 Max. Min.	17.451 Max. Min.	22.237 22.216	4 530	5 980	25 000	IRB 86	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952172989
Diametro interno	17.46 mm
Diametro interno	11/16" inch
Diametro esterno	22.23 mm
Diametro esterno	7/8" inch
Spessore	9.52 mm
Spessore	0.375" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE