


Gusci a rullini BAM1216-IKO - BAM1216-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1216-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
19.050 (3/4)	—	—	—	—	—	—	—	BAM 1216	28.5	—	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	F_w	Shaft dia. h6	Housing bore dia. J7	C	C_0	C_0	rpm		
Max.	Max.	Min.	Max.	Max.	Min.	N	N	N			
19.050	25.400	25.40	1.3	19.050	19.037	25.412	25.391	16 300	26 500	20 000	IRB 616-1

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173030
Diametro interno	19.05 mm
Diametro interno	3/4" inch
Diametro esterno	25.4 mm
Diametro esterno	1" inch
Spessore	25.4 mm
Spessore	1" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE