


Gusci a rullini BAM126-IKO - BAM126-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam126-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
19.050 (3/4)	—	—	—	—	—	—	—	BAM 126	11.7	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F _w	D	C	B ₂	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	Max. Min.	N	N	rpm	—	
19.050 3/4	25.400 1	9.521 .375	1.3	19.050 19.037	25.412 25.391	5.040	5.850	20.000	—		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173047
Diametro interno	19.05 mm
Diametro esterno	25.4 mm
Spessore	9.52 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE