


## Gusci a rullini BAM1312-IKO - BAM1312-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1312-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Identification number			Grease retained Mass (Ref.) g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end			
20.638 ( $\frac{3}{16}$ )	---	---	---	---	---	BAM 1312	23.5	---	
Boundary dimensions mm(inch)		Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	
F <sub>w</sub>	D	C	Shaft dia. h6	Housing bore dia. H7	N	N	rpm	IRB 912	
20.638 $\frac{3}{16}$	26.988 $\frac{1}{2}$	19.051 $\frac{3}{4}$	20.638 Max	20.625 Min	27.000 Max	26.979 Min	12 400	19 000	19 000

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173078
Diametro interno	20.64 mm
Diametro esterno	26.99 mm
Spessore	19.05 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE