


Gusci a rullini BAM1422-IKO - BAM1422-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1422-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
22.225 (7/8)	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾		Assembled inner ring			
F_w	D	C	B	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	rpm					
22.225 7/8	28.575 1 1/4	34.92 1.375	2.8	22.225 22.212	28.587 28.566	24 100	45 700	18 000					IRB 1022

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173177
Diametro interno	22.23 mm
Diametro esterno	28.58 mm
Spessore	34.92 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE