


Gusci a rullini BAM1516-IKO - BAM1516-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1516-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g																																				
	Standard	Mass (Ref.) g	Closed end																																														
23.812 ($\frac{9}{4}$)	---	---	---	---	---	---	---	---	---	---	---	---	---																																				
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions mm(inch)</th> <th colspan="4">Standard mounting dimensions mm</th> <th rowspan="2">Basic dynamic load rating C</th> <th rowspan="2">Basic static load rating C₀</th> <th rowspan="2">Allowable rotational speed^(*)</th> <th rowspan="2">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. h₈</th> <th>Housing bore dia. J7</th> <th>Max.</th> <th>Min.</th> <th>N</th> <th>N</th> <th>rpm</th> </tr> </thead> <tbody> <tr> <td>23.812</td> <td>$\frac{9}{4}$</td> <td>30.162</td> <td>$1\frac{1}{8}$</td> <td>25.40</td> <td>1.000</td> <td>2.8</td> <td>23.812</td> <td>23.799</td> <td>30.176</td> <td>30.151</td> <td>18 900</td> <td>34 300</td> <td>16 000</td> <td>IRB 1116</td> </tr> </tbody> </table>														Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	F _w	D	C	Shaft dia. h ₈	Housing bore dia. J7	Max.	Min.	N	N	rpm	23.812	$\frac{9}{4}$	30.162	$1\frac{1}{8}$	25.40	1.000	2.8	23.812	23.799	30.176	30.151	18 900	34 300	16 000	IRB 1116
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring																																							
F _w	D	C	Shaft dia. h ₈	Housing bore dia. J7	Max.	Min.					N	N	rpm																																				
23.812	$\frac{9}{4}$	30.162	$1\frac{1}{8}$	25.40	1.000	2.8	23.812	23.799	30.176	30.151	18 900	34 300	16 000	IRB 1116																																			

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173214
Diametro interno	23.81 mm
Diametro esterno	30.16 mm
Spessore	25.4 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE